

**PATENT**

**ATTORNEY DOCKET NO.: SCF-46**

UNITED STATES PATENT APPLICATION

FOR

## COATED FABRIC FOR LUGGAGE

BY

JOEY K. UNDERWOOD

AND

T. DOYLE KELLEY

1977 1978 1979 1980 1981 1982 1983 1984 1985 1986 1987 1988 1989 1990 1991 1992 1993 1994 1995 1996 1997 1998 1999 2000 2001 2002 2003 2004 2005 2006 2007 2008 2009 2010 2011 2012 2013 2014 2015 2016 2017 2018 2019 2020 2021 2022 2023 2024 2025 2026 2027 2028 2029 2030 2031 2032 2033 2034 2035 2036 2037 2038 2039 2040 2041 2042 2043 2044 2045 2046 2047 2048 2049 2050 2051 2052 2053 2054 2055 2056 2057 2058 2059 2060 2061 2062 2063 2064 2065 2066 2067 2068 2069 2070 2071 2072 2073 2074 2075 2076 2077 2078 2079 2080 2081 2082 2083 2084 2085 2086 2087 2088 2089 2090 2091 2092 2093 2094 2095 2096 2097 2098 2099 2100 2101 2102 2103 2104 2105 2106 2107 2108 2109 2110 2111 2112 2113 2114 2115 2116 2117 2118 2119 2120 2121 2122 2123 2124 2125 2126 2127 2128 2129 2130 2131 2132 2133 2134 2135 2136 2137 2138 2139 2140 2141 2142 2143 2144 2145 2146 2147 2148 2149 2150 2151 2152 2153 2154 2155 2156 2157 2158 2159 2160 2161 2162 2163 2164 2165 2166 2167 2168 2169 2170 2171 2172 2173 2174 2175 2176 2177 2178 2179 2180 2181 2182 2183 2184 2185 2186 2187 2188 2189 2190 2191 2192 2193 2194 2195 2196 2197 2198 2199 2200 2201 2202 2203 2204 2205 2206 2207 2208 2209 2210 2211 2212 2213 2214 2215 2216 2217 2218 2219 2220 2221 2222 2223 2224 2225 2226 2227 2228 2229 2230 2231 2232 2233 2234 2235 2236 2237 2238 2239 2240 2241 2242 2243 2244 2245 2246 2247 2248 2249 2250 2251 2252 2253 2254 2255 2256 2257 2258 2259 2260 2261 2262 2263 2264 2265 2266 2267 2268 2269 2270 2271 2272 2273 2274 2275 2276 2277 2278 2279 2280 2281 2282 2283 2284 2285 2286 2287 2288 2289 2290 2291 2292 2293 2294 2295 2296 2297 2298 2299 2300 2301 2302 2303 2304 2305 2306 2307 2308 2309 2310 2311 2312 2313 2314 2315 2316 2317 2318 2319 2320 2321 2322 2323 2324 2325 2326 2327 2328 2329 2330 2331 2332 2333 2334 2335 2336 2337 2338 2339 2340 2341 2342 2343 2344 2345 2346 2347 2348 2349 2350 2351 2352 2353 2354 2355 2356 2357 2358 2359 2360 2361 2362 2363 2364 2365 2366 2367 2368 2369 2370 2371 2372 2373 2374 2375 2376 2377 2378 2379 2380 2381 2382 2383 2384 2385 2386 2387 2388 2389 2390 2391 2392 2393 2394 2395 2396 2397 2398 2399 2400 2401 2402 2403 2404 2405 2406 2407 2408 2409 2410 2411 2412 2413 2414 2415 2416 2417 2418 2419 2420 2421 2422 2423 2424 2425 2426 2427 2428 2429 2430 2431 2432 2433 2434 2435 2436 2437 2438 2439 2440 2441 2442 2443 2444 2445 2446 2447 2448 2449 2450 2451 2452 2453 2454 2455 2456 2457 2458 2459 2460 2461 2462 2463 2464 2465 2466 2467 2468 2469 2470 2471 2472 2473 2474 2475 2476 2477 2478 2479 2480 2481 2482 2483 2484 2485 2486 2487 2488 2489 2490 2491 2492 2493 2494 2495 2496 2497 2498 2499 2500 2501 2502 2503 2504 2505 2506 2507 2508 2509 2510 2511 2512 2513 2514 2515 2516 2517 2518 2519 2520 2521 2522 2523 2524 2525 2526 2527 2528 2529 2530 2531 2532 2533 2534 2535 2536 2537 2538 2539 2540 2541 2542 2543 2544 2545 2546 2547 2548 2549 2550 2551 2552 2553 2554 2555 2556 2557 2558 2559 2560 2561 2562 2563 2564 2565 2566 2567 2568 2569 2570 2571 2572 2573 2574 2575 2576 2577 2578 2579 2580 2581 2582 2583 2584 2585 2586 2587 2588 2589 2590 2591 2592 2593 2594 2595 2596 2597 2598 2599 2600 2601 2602 2603 2604 2605 2606 2607 2608 2609 2610 2611 2612 2613 2614 2615 2616 2617 2618 2619 2620 2621 2622 2623 2624 2625 2626 2627 2628 2629 2630 2631 2632 2633 2634 2635 2636 2637 2638 2639 2640 2641 2642 2643 2644 2645 2646 2647 2648 2649 2650 2651 2652 2653 2654 2655 2656 2657 2658 2659 2660 2661 2662 2663 2664 2665 2666 2667 2668 2669 2670 2671 2672 2673 2674 2675 2676 2677 2678 2679 2680 2681 2682 2683 2684 2685 2686 2687 2688 2689 2690 2691 2692 2693 2694 2695 2696 2697 2698 2699 2700 2701 2702 2703 2704 2705 2706 2707 2708 2709 2710 2711 2712 2713 2714 2715 2716 2717 2718 2719 2720 2721 2722 2723 2724 2725 2726 2727 2728 2729 2730 2731 2732 2733 2734 2735 2736 2737 2738 2739 2740 2741 2742 2743 2744 2745 2746 2747 2748 2749 2750 2751 2752 2753 2754 2755 2756 2757 2758 2759 2760 2761 2762 2763 2764 2765 2766 2767 2768 2769 2770 2771 2772 2773 2774 2775 2776 2777 2778 2779 2780 2781 2782 2783 2784 2785 2786 2787 2788 2789 2790 2791 2792 2793 2794 2795

**TREATED FABRIC FOR LUGGAGE**

**Field of the Invention**

5           The present invention generally relates to fabrics that are useful in the construction of luggage. More particularly, the present invention is directed to luggage fabrics having improved abrasion resistance properties.

**Background of the Invention**

10           Fabrics that are appropriate for use in the construction of luggage must be durable and must be able to withstand weather conditions and other harsh conditions to which luggage is often subjected. In designing a fabric for use in the construction of luggage, it is important to look at various factors including abrasion resistance.

15           In the past, the abrasion resistant properties of fabrics used in the construction of luggage were improved primarily by changing the construction of the fabric. For example, the denier of the yarns, the weave of the fabric, and the materials used to produce the fabric were varied in order to optimize the properties of the fabric. For example,  
20           recently nylon fabrics historically used in ballistic applications have been used to construct luggage. These fabrics have proved to be very durable in luggage applications.

25           Although many advances have been made to improve the durability of luggage fabrics, a need still remains for a luggage fabric having enhanced abrasion resistant properties. In particular, a need exists for a process for improving the abrasion resistance of fabrics.

**Summary of the Invention**

          The present invention recognizes and addresses the foregoing needs, and others in the field of luggage fabrics.

30           The present invention is directed toward a fabric for constructing luggage. The fabric can be made, for instance, from multifilament yarns.

The multifilament yarns can be made from various materials including polyester, cotton, nylon, polypropylene and the like. In one preferred embodiment, the fabric is made from nylon yarns, such as yarns typically used to produce ballistic fabrics.

5 In accordance with the present invention, the fabric is treated with a chemical composition. In particular, the chemical composition is incorporated into the fabric such that the fabric has an abrasion resistance that is twice the abrasion resistance of the woven fabric not similarly treated.

10 In one embodiment, for instance, the chemical composition includes a fluorocarbon polymer composition. For example, the fluorocarbon polymer composition can be a dispersion of perfluoroalkyl and polyisocyanate polymers. The fluorocarbon polymer composition can be present in the treatment solution at an amount of less than about 5% solids, particularly less than about 3% solids, and more particularly at about 1% solids. The fluorocarbon polymer composition is applied to the fabric at an add on rate of about 1% add on of the fluorocarbon polymer based upon the weight of the fabric. Besides containing a fluorocarbon polymer composition, the chemical composition can also contain an emulsifier, wetting agents, drying agents, and water.

15 20 It has been discovered that the chemical composition greatly improves the abrasion resistance of the fabric. In fact, the addition of the chemical composition finish to the fabric will double the abrasion resistance of the fabric. In one embodiment, nylon fabrics used in ballistic applications are utilized as the base fabric. The fabric can have an abrasion resistance of at least 2500 cycles, particularly at least 3500 cycles, and more particularly at least 4000 cycles when finished with the chemical composition of the present invention.

25 30 Fabrics made in accordance with the present invention can have various constructions and characteristics. Depending upon the particular

application of the fabric, the fabric can be made from various materials, various yarns, and can have a wide range of basis weights.

In one embodiment, the fabric treated in accordance with the present invention can be made from yarns having a denier of from about 800 to about 1400, and particularly from about 1000 to about 1300. The fabric can have from about 30 to about 60 ends per inch, and particularly from about 40 to about 50 ends per inch. Further, the fabric can have from about 36 to about 46 picks per inch. The yarns can also be twisted if desired. For instance, the yarns can have from about 2 to about 5 twists per inch and particularly from about 2½ to about 3½ twists per inch.

The finished weight of the fabric can vary depending upon the particular application. For instance, the fabric can have a finished weight of from about 8 ounces per square yard to about 20 ounces per square yard, and particularly from about 10 ounces per square yard to about 15 ounces per square yard.

Other features and aspects of the present invention are discussed in greater detail below.

#### **Brief Description of the Drawings**

A full and enabling disclosure of the present invention, including the best mode thereof, to one of ordinary skill in the art, is set forth more particularly in the remainder of the specification, including reference to the accompanying figures, in which:

Figure 1 is a piece of luggage made in accordance with the present invention; and

Figure 2 is a partial cross-sectional view of the luggage illustrated in Figure 1.

Repeat use of reference characters in the present specification and drawings is intended to represent same or analogous features or elements of the present invention.

### **Definitions and Standardized Procedures**

The following definitions and procedures are offered in order to better describe and quantify the performance of luggage and fabrics made according to the present invention.

#### **Taber Abrasion Test**

The Taber Abrasion test measures the number of cycles required for an abrasion wheel to wear completely through the fabric. Specifically, the Taber Abrasion tests were performed by applying a 1000 gram weight to an H18 abrasion wheel and then spinning the wheel in contact with the fabric until a certain level of wear or abrasion was reached. The number of cycles the wheel completed before this level of wear or abrasion was reached serves as the Taber Abrasion measurement in the form of number of cycles.

#### **Grab Tensile Test**

The grab tensile test used herein measures breaking strength of a fabric when subjected to unidirectional stress. This test is known in the art and conforms to ASTM D 5034. The results are expressed in pounds to break. Higher numbers indicate a stronger fabric. The values noted herein, measured in pounds, represent the "load" or the maximum load or force, expressed in units of weight, required to break or rupture the specimen in a tensile test.

The grab tensile test uses two clamps, each having two jaws with each jaw having a facing in contact with the fabric sample. The clamps hold the fabric in the same plane, usually vertically, separated by approximately three inches and move apart at a specified rate of extension. Values for grab tensile strength are obtained using a sample size of 4 inches by 6 inches with a jaw facing size of 1 inch by 1 inch, and a constant rate of extension of 300 mm/minute. The sample is wider than the clamp jaws to give results representative of effective strength of yarns in the clamped width combined with additional strength contributed

by adjacent yarns in the fabric. Usually, a grab tensile strength test closely simulates fabric stress conditions in actual use. Results are reported as an average of three specimens and may be performed with the specimen in the cross direction or the machine direction.

#### 5 **Trap Tear Test**

The values noted herein for tear strength were obtained through use of the Trap Tear test. The trapezoid or "trap" tear test is a tension test that is useful in estimating the relative ease of tearing a fabric. It is particularly useful in the determination of any appreciable difference in strength between the machine and cross direction of the fabric. The entire width of the specimen is gripped between clamps, thus the test primarily measures the bonding or interlocking strength of individual yarns directly in the tensile load, rather than the strength of the composite structure of the fabric as a whole.

10 In conducting the trap tear test used herein, an outline of a trapezoid is drawn on a 3 inch by 6 inch specimen with the longer dimension in the direction being tested, and the specimen is cut in the shape of the trapezoid. The trapezoid has a 4 inch side and a 1 inch side which are parallel and which are separated by 3 inches. A small preliminary cut of 5/8 inches is made in the middle of the shorter of the parallel sides.

15 The specimen is clamped into a testing device that has 3 inch long parallel clamps. The specimen is clamped along the non-parallel sides of the trapezoid so that the fabric on the longer side is loose and the fabric along the shorter side taut, and with the cut halfway between the clamps. A continuous load is applied on the specimen such that the tear propagates across the specimen width. It should be noted that the longer direction is the direction being tested even though the tear is perpendicular to the length of the specimen. The force required to completely tear the specimen is recorded in pounds with higher numbers

indicating a greater resistance to tearing. The test method used conforms to ASTM D-5587 except that the tearing load is calculated as the average of the first and highest peaks recorded rather than the lowest and highest peaks. Five specimens for each sample are usually tested.

### **Raveled Strip Test**

The Raveled Strip test was also performed on fabric samples made according to the present invention. The Raveled Strip test is a test for determining the breaking force and elongation of most textile fabrics. The test method used was a modified version of ASTM D 5035. The only modification made herein to the standard test method was to change from 1 inch wide strips to 10 mm wide strips in order to test only the abraded area of a test specimen or the area already subjected to the Taber Abrasion test.

In general, according to the Raveled Strip test, a test specimen is clamped in a tensile testing machine and a force is applied to the specimen until it breaks. Values for the breaking force and elongation of the test specimen are obtained and recorded.

### **Detailed Description of Preferred Embodiments**

It is to be understood by one of ordinary skill in the art that the present discussion is a description of exemplary embodiments only, and is not intended as limiting the broader aspects of the present invention, which broader aspects are embodied in the exemplary construction.

In general, the present invention is directed to a fabric suitable for use in the construction of luggage that has significantly improved abrasion resistant properties. In particular, the present invention is directed to a luggage fabric treated with a chemical composition, such as a durable water resistant composition. The present inventors discovered that the durable water resistant composition not only makes the fabric water resistant, but also imparts abrasion resistance to the fabric. In one

embodiment, the water resistant finish may include a fluoropolymer.

Referring to Figure 1, one embodiment of a piece of luggage generally 10 constructed in accordance with the present invention is illustrated. It should be understood that the fabric of the present invention can be used in any suitable type of luggage or bag. In the embodiment illustrated in Figure 1, luggage 10 includes a first side 14 connected to a second side 16 by a zipper 18. Luggage 10 further includes a handle 12 and optionally can include wheels and rollers for moving the luggage once filled. Further, the luggage can include various additional compartments as desired.

As shown, luggage 10 is made from a fabric 20. Fabric 20 is made from woven polymeric yarns.

As shown in Figure 2, fabric 20 includes a water barrier layer 21 applied to the inside surface of the fabric. The water barrier layer 21 can be made from various materials, such as polyurethanes, urethanes or a polyvinyl chloride film.

In accordance with the present invention, the exterior surface of the fabric includes a chemical composition 22. The chemical composition 22, applied to the fabric in accordance with the present invention has been found to be extremely durable and well suited for use in luggage applications. It was also discovered that the chemical composition significantly improves the abrasion resistance of the fabric. In particular, it was discovered by the present inventors that the chemical composition of the present invention can more than double the abrasion resistance of the fabric. In other words, a fabric treated in accordance with the present invention will have an abrasion resistance two times higher than the untreated fabric itself.

Fabrics that are suitable for use in the process of the present invention may be manufactured with yarns made of nylon, polyester, cotton, polypropylene, polyethylene, mixtures thereof, and other similar



yarns. For most applications, however, nylon is preferred. For example, in one embodiment, nylon yarns can be used that have been used in the past in ballistic applications.

5 The yarns used in the fabric to be treated with the water resistant, abrasion resistant treatment may be woven into various constructions. For instance, the fabric of the present invention can have a basket weave or a plain weave. Any other suitable weave may be employed, for example such as a ripstop weave or a twill weave.

10 The weight of the fabric made in accordance with the present invention can vary and generally will depend upon the particular application for which the fabric is used. For most applications, however, the fabric can have a weight of from about 4 ounces per square yard to about 20 ounces per square yard. When used to construct luggage, the fabric will generally have a weight of from about 10 ounces per square  
15 yard to about 15 ounces per square yard, and particularly from about 11 ounces per square yard to about 14 ounces per square yard. In general, the yarns used to construct the fabric are multifilament yarns, although it is believed that monofilament yarns may be used in some applications. The denier of the yarns again will vary depending upon the type of  
20 product being formed with the fabric. In general, however, the denier of the yarns can be from about 100 to about 2000, particularly from about 390 to about 1600 and, in one embodiment, from about 1000 to about 1300. For example, the denier of the yarns can be from about 1050 to about 1260.

25 When using multifilament yarns, it may also be desirable to incorporate twists into the yarn, prior to forming the fabric. For instance, the yarns can have from about 2 to about 5 twists per inch, and particularly from about 2½ to about 3½ twists per inch.

30 When using yarns within the above described denier ranges, the woven fabric of the present invention can have from about 30 ends to

about 60 ends per inch, which refers to the warp yarn density. More particularly, the fabric can have from about 40 to about 45 ends per inch. The number of picks, which refers to the fill yarn density, on the other hand, can generally vary from about 36 picks per inch to about 46 picks per inch.

As described above, once the fabric of the present invention is constructed, generally first a water impermeable barrier layer is applied to the inside surface of the fabric. The water impermeable coating can be a film either extruded onto or laminated to the fabric. The film can be made from a urethane, a polyurethane, polyvinyl chloride or other suitable material.

Once the water impermeable coating is applied to the fabric, a finish is then applied to the opposite side of the fabric in accordance with the present invention. As discussed above, when applied according to the present invention, it has been discovered that the finish is very durable and wear resistant. Further, the finish has also been found to improve the abrasion resistance properties of the fabric.

In one embodiment of the present invention, the chemical composition is made from a solution of a fluorocarbon polymer that is applied to the fabric. For example, the chemical composition can be made from TEFLON polymers which are commercially available from DuPont. Fluorocarbon polymer solutions containing TEFLON polymers are also commercially available from other numerous sources. In one particular embodiment of the present invention, the fluorocarbon polymer composition includes a dispersion of perfluoroalkyl and polyisocyanate polymers.

Besides containing a fluorocarbon polymer, the chemical composition can also contain various other additives. For instance, in one embodiment, the chemical composition can contain a fluorocarbon polymer, an emulsifier, an alcohol, and water. The emulsifier can be, for

instance, acetic acid. The chemical composition may also contain a binder, such as an acrylic binder.

In one embodiment, the finish composition can contain from about 2 percent to about 30 percent by weight of a fluorocarbon polymer composition, and particularly from about 4 percent to about 10 percent by weight of the bath. The finish composition can contain about 1% active solids, that is, the fluorocarbon solids. Further, the treatment can contain an emulsifier in an amount from about 7 percent to about 25 percent by weight, and particularly from about 10 percent to about 20 percent by weight of the bath.

In one particular embodiment of the present invention, the fluorocarbon polymer composition contains about 8% by weight of a fluorocarbon polymer (containing about 1% active solids), such as ZONYL FMX treatment available from Ciba Specialty Chemicals Corporation of Highpoint, North Carolina. The composition can further contain about 16% by weight of an emulsifier, such as ULTRATEX REP emulsifier also available through Ciba Specialty Chemicals Corporation, about 1 to about 3% by weight of an alcohol, such as isopropanol, and the remainder water.

In order to produce a liquid resistant fabric in accordance with the present invention, after the woven fabric is constructed, the fabric can first be scoured, although scouring may not be necessary for all applications.

After scouring, the fabric will be dried. If desired, the fabric will then be dyed to the desired color by any suitable method. At that point, a water barrier layer may be coated onto what will be the inner surface of the fabric on the final product.

After these processing steps, a chemical composition according to the present invention is supplied to at least one side of the fabric.

Although the treatment can be sprayed on the fabric or printed on the

fabric, preferably the fabric is dipped into a bath containing the chemical composition in solution form.

As stated above, the chemical composition in one embodiment, can be a solution containing a fluorocarbon polymer. The fluorocarbon polymer can be combined in the solution with water, a drying agent such as an alcohol, and an emulsifier. The amount of the water-resistant composition applied to the fabric will depend upon the particular formulation and the particular application.

In one embodiment, the composition is applied to the fabric at a wet pick up rate of from about 10% to about 50% by weight of the fabric, particularly from about 15% to about 30% by weight, and in one embodiment, at a wet pick up rate of about 18 - 20% by weight of the fabric.

After the chemical composition is applied to the fabric, the fabric is then heated to a temperature sufficient for the finish to dry and/or cure. In one particular embodiment, the finish may be cured by heating the fabric to a temperature of about 390°F for approximately 1 ½ minutes. Once the chemical composition is cured and affixed to the woven fabric, the fabric can then be used in constructing luggage and other articles in accordance with the present invention.

The chemical composition of the present invention makes the fabrics water resistant and also improves the abrasion resistance of the fabric. The abrasion resistance of the fabric of the present invention is of great importance in that luggage made with the fabric is better able to withstand wear-and-tear. For instance, fabrics made in accordance with the present invention can have abrasion resistance ratings of at least 2000 cycles, such as from 3000 - 5000 cycles. In other embodiments, durable fabrics made according to the present invention have abrasion resistance ratings of up to and over 6000 cycles. Of particular importance, it has been discovered that the abrasion resistance of

fabrics treated according to the present invention are more than double in comparison to similar untreated fabrics.

Preferred embodiments of the present invention involve the use of the treated water resistant and abrasion resistant fabric in the construction of luggage. However, other items that benefit from improved abrasion resistance may be constructed from the fabric described herein. For example, skates, sportswear, mountain climbing apparel, hockey apparel, skiwear, marine wear, awnings, military apparel, and the like may be constructed using the treated fabric of the present invention.

The present invention may be better understood with reference to the following examples.

#### **EXAMPLE 1**

Two different fabric constructions, Fabric A and Fabric B, were tested for various properties. Both of these fabric constructions are suitable for use as luggage fabrics according to the invention herein. Both fabric constructions were of multifilament yarns made of nylon. Specifically, the nylon yarns were obtained from Honeywell, Inc. The yarns were woven into a basket-type weave.

Different chemical finishes were applied to the two fabrics. Fabric A as treated may be obtained from Travis Textiles, Inc. of New York, New York. It is sold under the name Tru Ballistic and was treated with a finish containing SEQUAPEL WFC sold by Omnova of Chester, South Carolina. Sequapel WFC is known to be a fluorocarbon.

The chemical composition of the finish of Fabric B contained 5.2% by weight of a fluorocarbon polymer (ZONYL FMX obtained from Ciba Specialty Chemicals Corp.) composition which contained a dispersion of perfluoroalkyl and polyisocyanate polymers. In addition to the fluorocarbon polymer composition, the finish of Fabric B also contained an emulsifier (ULTRATEX REP obtained from Ciba Specialty Chemicals

Corp.) in an amount of 10.4% by weight.

The treatment applied to Fabric B was applied to the fabrics as described above in the detailed description. The fabric had a 1% add on of the fluorocarbon polymer by weight of the fabric.

5 Tests were performed to examine several properties of the fabrics. The specifications of the fabrics and the results of the testing are described below in Table I.

**TABLE I**

<b>Fabric Specifications</b>	<b>Fabric A (Prior Art)</b>	<b>Fabric B</b>
Warp Yarn Denier	1050	1050
Fill Yarn Denier	1050	1260
Warp Yarn Twists/Inch	2.5	2.5
Fill Yarn Twists/Inch	2.5	3.5
Warp Yarn Count (Yarns/Inch)	43	43
Fill Yarn Count (Yarns/Inch)	42	40
Warp Grab Tensile (lbs.)	981	987
Fill Grab Tensile (lbs.)	941	984
Warp Tear Strength (lbs.)	217	263
Fill Tear Strength (lbs.)	212	341
Raveled Strip (lbs.) of nonabraded strip	275	293
Raveled Strip (lbs.) of abraded strip	15	80

**EXAMPLE 2**

In this Example, several samples of finished fabrics were tested for improved abrasion resistance in comparison to the prior art fabric (Fabric A) described in Example 1. All of the samples were made with

5 nylon multifilament yarns. All fabrics made in accordance with the present invention had a finish add on of 1% add on of the fluorocarbon polymer by weight of the fabric. The treated samples varied in denier and in fill yarn count (picks). The samples also varied in chemical composition of the finish. Sample number 1 used the standard industry finish used on Fabric A in Example 1. The other samples used the 5.2% by weight fluorocarbon polymer composition used on Fabric B in Example 1. The fabric samples' specifications and the results of the Taber Abrasion testing are described in Table 2 below:

00723600 420400  
007027 00932260

Table 2

Sample Number	1 (Fabric A - Prior Art)	2	3	4	5	6	7
Warp Yarn Denier	1050	1050	1050	1050	1050	1050	1050
Fill Yarn Denier	1050	1260	1050	1050	1050	1260	1260
Ends	43	43	43	43	43	43	43
Picks	42	40	42	44	46	36	38
Weight (OSY)	12.3	13.23	12.3	12.65	12.94	12.53	12.88
wt.% Fluorocarbon Polymer in Finish	N/A	5.2	5.2	5.2	5.2	5.2	5.2
Taber Abrasion Cycles (Range)	1975- 2400	3950- 5000	3500- 4500	5000- 6700	4500- 7650	—	—
Taber Abrasion Cycles (Average)	2091	4377	4264	5865	5887	4500	5500

As shown above, all of the fabrics made in accordance with the present invention had much better abrasion resistance properties than Sample No. 1. It was also discovered that adding fill yarns increased the abrasion resistant properties of the fabric (compare Sample No.4 to Sample No.5). It was also



discovered that fill yarns can be removed without adversely affecting abrasion resistance if the denier of the yarn was also increased (compare Sample No.4 with Sample No.7)

### **Example 3**

5 In this example, the abrasion resistance of a fabric treated in accordance with the present invention was compared to a control fabric having the same construction but not chemically treated.

10 The fabric tested in this example was made with nylon multifilament yarns and had the same construction as Fabric B of Example 1. A polyurethane coating was applied to one side of the fabric. Three different samples of the fabric were then treated in accordance with the present invention. In particular, the fabric was treated with a chemical composition containing 5.2% by weight ZONYL FMX obtained from Ciba Specialty Chemicals Corporation, 16% by weight ULTRATEX REP also obtained from Ciba Specialty Chemicals Corporation, about 1% by weight isopropanol and about 74% by weight water. The composition was applied to the fabric at a wet pick-up rate of 19% of the weight of the fabric. The samples were then tested for abrasion resistance. Control samples not treated with the chemical composition were also tested for abrasion resistance. The following results were obtained:

**TABLE 3**

SAMPLE NUMBER	TABER ABRASION CYCLES	
	Control	Treated Fabric
1	1985	2690
	1990	4000
	1985	3878

	1987 (Avg)	3523 (Avg)
2	1675	3998
	1123	3484
	1980	4376
	1593 (Avg)	3953 (Avg)
3	2161	4980
	1500	2530
	1300	5300
	1654 (Avg)	4270 (Avg)
Overall Average	1744	3915

As shown above, fabrics treated in accordance with the present invention generally have an abrasion resistance rating of at least 3000 cycles. As also shown above, treating the fabrics in accordance with the present invention more than doubled the abrasion resistant properties of the fabric.

These and other modifications and variations to the present invention may be practiced by those of ordinary skill in the art, without departing from the spirit and scope of the present invention, which is more particularly set forth in the appended claims. In addition, it should be understood that aspects of the various embodiments may be interchanged both in whole or in part. Furthermore, those of ordinary skill in the art will appreciate that the foregoing description is by way of example only and is not intended to limit the invention so further described in such appended claims.